



NOTES - ALL RESISTORS IN OHMS 1/2W 10% UNLESS OTHERWISE SPECIFIED
 - ALL CAPACITORS IN MFD AND 400V 10% UNLESS OTHERWISE SPECIFIED.
 - D.C. VOLTAGE READINGS WITH NO SIGNAL APPLIED USING A 20,000 Ω PER VOLT VOLTMETER.
 - NUMBERS IN PARENTHESES REFER TO AMPEG S PART NO.
 * 2A FUSE SHOULD BE IN 240V MODELS ONLY
 - D.C. VOLTAGE READINGS ARE POSITIVE WITH RESPECT TO GROUND UNLESS OTHERWISE SPECIFIED
 - CIRCUIT OF CHASSIS MAY VARY SLIGHTLY FROM THAT SHOWN HERE DUE TO NORMAL PRODUCTION CHANGES
 ** -RES. 60, 61, 62, 63 & 64 ARE LOCATED ON SW1.
 * -THE P.T. FOR 240V MODELS HAS BLACK WIRE CONNECTED TO BLUE WH. AS DOTTED LINE SHOWS

MODEL B155
 U.S. PATENT PENDING

| | | | |
|-------------|----------|----------|----------|
| DRN BY DATE | DWG. NO. | PART NO. | REV. |
| S. C. | 3-71 | 06400 | 40102580 |
| S. C. | | 3-71 | 06400 |
| S. C. | | 3-71 | 06400 |

