

NOTES
- ALL RESISTORS IN OHMS 1/2W 10% UNLESS OTHERWISE SPECIFIED.
- ALL CAPACITORS IN MFD AND 400V 10% UNLESS OTHERWISE SPECIFIED.
+ D.C. VOLTAGE READINGS WITH NO SIGNAL APPLIED USING A 20,000 Ω PER VOLT VOLTMETER.
- NUMBERS IN PARENTHESIS REFER TO AMPEG'S PART NO.
* 2A FUSE SHOULD BE IN 240V MODELS ONLY.
- D.C. VOLTAGE READINGS ARE POSITIVE WITH RESPECT TO GROUND UNLESS OTHERWISE SPECIFIED.
- CIRCUIT OF CHASSIS MAY VARY SLIGHTLY FROM THAT SHOWN HERE DUE TO NORMAL PRODUCTION CHANGES.
** RES. 60, 61, 62, 63 & 64 ARE LOCATED ON SW1.
* - THE P.T. FOR 240V MODELS HAS BLCK WIRE CONNECTED TO BLUE WH. AS DOTTED LINE SHOWS.

ampeg
POST OFFICE BOX 310
LINDEN, NEW JERSEY

MODEL
B15S
U.S. PATENT PENDING

DRN. BY	DATE	DWG. NO.	PART NO.	REV.
S. C.	3-71	06400	40102580	C