



NOTES: - ALL RESISTORS IN OHMS  $\frac{1}{2}$ W 10% UNLESS OTHERWISE SPECIFIED.  
 - ALL CAPACITORS IN MFD. & 400V UNLESS OTHERWISE SPECIFIED.  
 - D.C. VOLTAGE READINGS WITH NO SIGNAL APPLIED USING A 20000 $\Omega$  PER VOLT VOLTMETER.  
 - NUMBERS IN PARENTHESES REFER TO AMPG'S PART NO.  
 - PARTS DESIGNATED BY \* ARE IN 240V MODELS ONLY. THE P.T. FOR 240V MODELS HAS BLACK WIRE CONNECTED TO BLUE WIRE.  
 - D.C. VOLTAGE READINGS ARE POSITIVE WITH RESPECT TO CHASSIS GROUND UNLESS OTHERWISE SPECIFIED.  
 - CIRCUIT OF CHASSIS MAY VARY SLIGHTLY FROM THAT SHOWN HERE DUE TO NORMAL PRODUCTION CHANGES.  
 - D1-4 ARE SILICON AX TYPE 1AMP. 1400 VOLTS DIODES.

POST OFFICE BOX 218  
 NEW YORK, NEW JERSEY

**ampeg**

MODEL V2  
 U.S. PATENT PENDING.

DRN BY	DATE	DWG. NO.	PART NO.	REV.
GC	671	06-800	400268	B