





FIGURE VI - 2. SCHEMATIC - 950 - 970 SERIES

NOTES:

1. SWITCHES SHOWN IN CCM POSITION - 72 INS POSITION - PL-ARC POSITION
2. V1, V2, V3, V4, V5, V6, V7, V8, V9, V10, V11, V12, V13, V14, V15, V16, V17, V18, V19, V20, V21, V22, V23, V24, V25, V26, V27, V28, V29, V30, V31, V32, V33, V34, V35, V36, V37, V38, V39, V40, V41, V42, V43, V44, V45, V46, V47, V48, V49, V50, V51, V52, V53, V54, V55, V56, V57, V58, V59, V60, V61, V62, V63, V64, V65, V66, V67, V68, V69, V70, V71, V72, V73, V74, V75, V76, V77, V78, V79, V80, V81, V82, V83, V84, V85, V86, V87, V88, V89, V90, V91, V92, V93, V94, V95, V96, V97, V98, V99, V100
3. M-DC-10M, R-0000 OHM
4. ALL NON-ELECTRIFYING CAPACITORS CAPACITY IN MICROGRAMS-KILOVOLTS, UNLESS OTHERWISE NOTED
5. ALL RESISTORS, 1/2 WATT 10%, UNLESS OTHERWISE NOTED
6. S, Z, B, S, 3 ARE CONCENTRIC SWITCHES.
7. ALL DC RECORDING SWITCHES SHOULD BE OPENED WITH A 20,000 OHM PER VOLT RESISTOR.
8. ALL AC VOLTAGES MEASURED WITH AN AC VOLT/AMPERE METER WITH THE METER IN THE EQUALIZER LINE, VOLUME CONTROL WITH VOLUME REMOVED AND A 20,000 OHM PER VOLT RESISTOR IN THE EQUALIZER LINE. ALL AC VOLTAGES MEASURED WITH A 20,000 OHM PER VOLT RESISTOR IN THE EQUALIZER LINE.
9. THERMAL RESISTANCE ADJUSTED TO PROVIDE OPTIMUM TUBE LIFE.
10. ON MULTIPLE OR GANGED PARTS, AMPER PART NUMBER IS NOTED ON FIRST OR A SECTION.