



(COMPONENT VALUE CHART)

ITEM	PS-200/ PL3 MODELS	PS-400/ PL4 MODELS
C2	18000uf/35 VDC	18000uf/70 VDC
C3	3300uf/35 VDC	1800uf/70 VDC
D104/D204	JUMPER	D104/ D204
D106/D206	JUMPER	D106/ D206
R130/R230	24 K	OPEN
R132/R232	OPEN	174 K
R133/R233	5.1 K	4.7 K
R134/R234	OPEN	174 K
R136/R236	22.1 K	OPEN

DEDICATED TO THE MEMORY OF RICHARD PLATER FROM THE ENGINEERING DEPT.

PL FOUR SCHEMATIC NOTES

- THIS IS A REPRESENTATIVE SCHEMATIC ONLY AND DOES NOT NECESSARILY REFLECT THE EXACT CIRCUITRY OF YOUR UNIT. PLEASE REFER TO THE RESPECTIVE SERVICE MANUAL FOR FURTHER TECHNICAL INFORMATION.
- CIRCUIT SHOWN APPLIES TO UNITS WITH SN3024 AND ABOVE.
- ALL RESISTORS ARE IN OHMS, ALL CAPACITORS IN MICROFARADS UNLESS OTHERWISE DESIGNATED.

- ALL RESISTORS ARE .25 WATT, 5% TOLERANCE UNLESS OTHERWISE DESIGNATED.
- COMPONENTS COMMON TO BOTH CHANNELS ARE NUMBERED FROM 1 TO 99.
- LEFT CHANNEL COMPONENTS ARE NUMBERED FROM 100 TO 199.
- RIGHT CHANNEL COMPONENTS ARE NUMBERED FROM 200 TO 299.

- MONO/STEREO SWITCH SHOWN IN THE MONO POSITION.
- +VCC IS 62 VOLTS.