CHANNEL 1



CHANNEL 2



NOTES:
UNLESS
1. ALL
2. ALL
3. ALL
4. ALL
5. ALL
6. ALL
7. ALL
8. SELE
SELE
SELE
PROC
9. ▽ D
R









NOTES:
UNLESS OTHERWISE SPECIFIED:
1. ALL RESISTORS ARE EXPRESSED IN OHMS AND ARE 1/4W, 5%.
2. ALL CAPACITORS ARE EXPRESSED IN MICROFARADS.
3. ALL MYLAR CAPACITORS ARE +/-5%.
4. ALL NPO AND S2L CERAMIC DISC CAPACITORS ARE +/-5%.
5. ALL Y5E CERAMIC DISC CAPACITORS ARE +/-10%.
6. ALL POLYPROPYLENE CAPACITORS ARE +/-2.5%.
7. ALL RADIAL ELECTROLYTIC CAPACITORS ARE +/-20% AND ARE LOW LEAKAGE.
8. SELECT A 10 MFD ELECTROLYTIC CAPACTOR (C26 AND C126) WITH SELECTION PROCEDURE [illegible] GROUP A OR B.
   SELECT RESISTOR (R30 AND R130) WITH SELECTION PROCEDURE [illegible] GROUP A OR B.
9. ▽ DENOTES GROUNDS ARE TIED CLOSELY TOGETHER AND RETURN TO CENTRAL GROUND SEPARATELY.