



POA-6800

NOTES
 ALL RESISTANCE VALUES IN OHMS, K = 1,000 OHMS, M = 1,000,000 OHMS.
 ALL CAPACITANCE VALUES IN PICO FARADS, K = 1,000 FARADS, M = 1,000,000 FARADS.
 EACH VOLTAGE AND CURRENT ARE MEASURED AT NO SIGNAL INPUT CONDITION.
 CIRCUIT AND PARTS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

▲ Means important safety item, which must be replaced, when necessary, by a part specified or meeting the specification by the manufacturer.

RESISTANCE		CAPACITANCE	
EU	EU	EU	EU
E1	2.2/70W	E1	1000.000
E2	4.7/70W	E2	100.000
E3		E3	10.000
E4		E4	1.000
E5		E5	0.100
E6		E6	0.010
E7		E7	0.001
E8		E8	0.0001
E9		E9	0.00001

POWER TRANS.		DIODE	
EU	EU	EU	EU
E1	2.2/70W	E1	1000.000
E2	4.7/70W	E2	100.000
E3		E3	10.000
E4		E4	1.000
E5		E5	0.100
E6		E6	0.010
E7		E7	0.001
E8		E8	0.0001
E9		E9	0.00001

