



**LEGEND**

**RESISTORS**  
 HALF WATT UNLESS OTHERWISE NOTED.  
 10% TOL. UNLESS OTHERWISE NOTED.  
 K=1,000  
 M=1,000,000

**CAPACITORS**  
 TUBULAR, CAPACITY IN ufd., & D.C.W.V.  
 CURVED LINE OUTSIDE FOIL.  
 + ELECTROLYTIC, CAPACITY IN ufd., & D.C.W.V.  
 - CERAMIC, MICA, OR OTHER TYPES WITH NO OBVIOUS OUTSIDE OR GROUNDED SIDE.  
 CAPACITY IN ufd., TOL. IF CRITICAL, & D.C.W.V.

\* C20 5K

\* C17 5K

P3

P2

**SPECIAL CAPACITORS SUCH AS TEMPERATURE COMPENSATING TYPES ARE IDENTIFIED BY A NOTE AT CAPACITOR LOCATION.**  
 eg O.F. = OIL FILLED  
 S.M. = SILVER MICA  
 M = MICA  
 N.P. = NON POLARIZED  
 P.Y. = POLYSTYRENE

POWER SUPPLY FOR SELF-POWERED UNITS  
**ELECTROHOME MP-3 & MXA-3 VIKING VMXA-3**