



**CAUTION** 500 VOLTS AVAILABLE. DISCONNECT POWER SUPPLY BEFORE SERVICING AND ALLOW 30 SECONDS MINIMUM FOR BLEEDERS TO DISSIPATE 8V VOLTAGES.

**TEST DATA**

**MV** DENOTES TYPICAL 1K $\Omega$  SIGNAL FOR 10 WATTS OUTPUT AND 450MV REVERB INPUT UNIT DRIVE.  
**▲** INSERT BLANA PLUG INTO INPUT JACK FOR THIS TEST.  
 CONTROL SETTINGS- EQUALIZERS AT MID POSITION, DISTORTION PRESENCE AT MINIMUM, OTHERS AT MAXIMUM.

XA-USE 0.1MFD 600V CAPACITOR IN SERIES WITH GENERATOR.  
 D.C. VOLTAGES READ WITH NO SIGNAL INPUT AND DISTORTION OFF $\dagger$ .

**▲** 035604 CONDUCTS WITH DISTORTION ON.

**FENDER MUSICAL INSTRUMENTS**

CBS MUSICAL INSTRUMENTS  
 A DIVISION OF CBS INC.  
 FULLERTON CALIFORNIA  
 U.S.A.

3. USED IN SOME VERSION.
2. ALL RESISTORS ARE 1/2W, 10%.  
 1. ALL CAPACITORS AT LEAST 600 V.D.C.

NOTES: UNLESS OTHERWISE SPECIFIED

**Fender/Reverb/Rhodes**  
© 1964 FENDER MUSIC INSTRUMENTS, INC. FULLERTON, CALIF.  
 - SCHEMATIC -  
 180 WATT  
 SUPER TWIN REVERB  
 013606