



**CAUTION**  
TURN OFF POWER  
BEFORE REMOVING  
TUBES

VOLTAGE & RESISTANCE READINGS  
FUNCTION SWITCH IN AM POSITION  
STEREO SWITCH IN MON. POSITION  
LOGIC/LEVEL CONTROL, MIN. CCW  
CONTORL SW. ON, LINE MON. OUT  
TONE CONTROL, MIN. CCW  
BALANCE CONTROL, IN STEREO  
BASS & TREBLE CONTROL, FLAT  
BALANCE CONTROL, CENTERED

RESISTANCE READINGS

ITEM	TUBE	PN 1	PN 2	PN 3	PN 4	PN 5	PN 6	PN 7	PN 8
V1	12AX7	100K	100K	100K	100K	100K	100K	100K	100K
V2	12AX7	100K	100K	100K	100K	100K	100K	100K	100K
V3	12AX7	100K	100K	100K	100K	100K	100K	100K	100K
V4	7199	100K	100K	100K	100K	100K	100K	100K	100K
V5	7199	100K	100K	100K	100K	100K	100K	100K	100K
V6	7591	100K	100K	100K	100K	100K	100K	100K	100K
V7	7591	100K	100K	100K	100K	100K	100K	100K	100K
V8	7591	100K	100K	100K	100K	100K	100K	100K	100K
V9	7591	100K	100K	100K	100K	100K	100K	100K	100K

NOTES  
1- ALL RESISTANCE VALUES IN OHMS UNLESS SPECIFIED  
2- ALL RESISTANCE VALUES IN OHMS UNLESS SPECIFIED  
3- ALL RESISTORS 1/2 WATT  
4- ALL CAPACITORS WITH DECIMAL VALUES IN UG.  
5- ALL CAPACITORS WITHOUT DECIMAL VALUES IN UG.  
6- ALL VOLTAGES ARE DC UNLESS NOTED OTHERWISE

\* RESISTANCE READINGS MARKED WITH ASTERISK ARE MEASURED FROM THE JUNCTION OF RESISTORS

8728  
12287954

A700