



- SPECIFICATIONS**
- DYNAMIC POWER OUTPUT (IHF):**
 - 30 watts both channels at 4 ohms
 - 26 watts both channels at 8 ohms
 - CONTINUOUS POWER OUTPUT:**
 - Each Channel Driven: 11/11 watts at 4 ohms, 10/10 watts at 8 ohms
 - Both Channels Driven: 8.5/8.5 watts at 4 ohms, 8/8 watts at 8 ohms
 - HARMONIC DISTORTION:**
 - Less than 0.8% at rated output
 - Less than 0.2% at -3 dB rated output
 - INTERMODULATION DISTORTION:**
 - Less than 0.8% at rated output
 - FREQUENCY RESPONSE:**
 - 1DS; Crossover freq. ~ 30 kHz ± 2 dB
 - 4 CH; 25 ~ 30 kHz ± 2 dB
 - POWER BANDWIDTH:**
 - 40 ~ 20 kHz ± 2 dB
 - INPUT SENSITIVITY (for rated output):**
 - 100 mV
 - LOW OUTPUT (IDS):**
 - 80 mV
 - RECORDING OUTPUT:**
 - 100 mV
 - HUM AND NOISE:**
 - Less than 1 mV
 - DAMPING FACTOR:**
 - 50 at 8 ohms
 - SPEAKER IMPEDANCE:**
 - 4 ~ 16 ohms
 - BASS CONTROL:**
 - ± 8 dB at 100 Hz
 - TREBLE CONTROL:**
 - ± 8 dB at 10 kHz
 - LOUDNESS CONTROL (at -30 dB):**
 - 8 dB ± 3 dB at 100 Hz
 - CROSSOVER FREQUENCY:**
 - 400, 800, 5000 Hz
 - SEMICONDUCTORS:**
 - 31 transistors, 6 diodes, 3 SCR's
 - POWER VOLTAGE:**
 - 110 - 120V/220 - 240V 50/60 Hz
 - POWER CONSUMPTION:**
 - 80 watts at full power
 - DIMENSIONS:**
 - 16-1/4" (W) x 4-3/4" (H) x 12" (D) (inches)
 - WEIGHT:**
 - 16-1/2 lbs.