



POWER OUTPUT

55 watts* per channel minimum RMS, both channels driven, at 8 ohms from 20 Hz to 20,000 Hz with no more than 0.05% total harmonic distortion.

- 80-60 watts 8 ohms at 1,000 Hz
- 70-70 watts 4 ohms at 1,000 Hz
- 0.05% at rated power into 8 ohms
- 0.008% at rated power into 4 ohms
- 0.01% at 1/2 rated power into 8 ohms
- 0.05% at rated power with VOLUME 20 dB
- 0.009% at rated power into 8 ohms
- 45-20 Hz - 20,000 Hz into 8 ohms
- 1.4:1
- 1.70 V AS
- 5 Hz to 40,000 Hz at 0.05% THD
- 2 Hz to 250 kHz, 3 dB
- Attenu 4 ohms to 16 ohms
- 2.5 mv 50 khzms
- 150 mv 30 khzms
- 150 mv 30 khzms
- 2.5 mv 50 khzms
- Signal to Noise Ratio (HF, A1)
- Temp. AUX. Tone
- Maximum Input Level for Phono
- Output Level Impedance
- Temp. REC (Dist)
- Frequency Response for Phono
- Tone Control
- Bass
- Treble
- Loadable Control
- Power Consumption
- A.C. Output
- Dimensions
- Weight (Net)

*Maximum Power Output is limited by the Power Amplifier's Thermal Characteristics.

Note: Kenwood follows a policy of continuous advancements in development. For this reason specifications may be changed without notice.