



System Super-Low Frequency Drive System

Mounted Speakers

Driver 200 mm (8 inch) Cone Type x 1
 Passive Cone 400 mm (16 inch) Cone Type x 1

Mounted Amplifier

Power Output 40 watts minimum RMS, 8 ohms at 20 Hz with no more than 0.8% Total Harmonic Distortion
 More than 10k ohms

Input Impedance

Input Sensitivity 1 volt
 Output Sensitivity 96 dB/W at 1 m (Volume Level MAX)

Cut off Frequencies

50 Hz, 100 Hz, 150 Hz, (12 dB/oct)

Additional Features

Level Control with 10 LED Level Indicators and 1 LED Peak Indicator
 Locked type Casters

Power Requirements

120/240V (Switchable), 50/60 Hz

Power Consumption

40 watts at full power
 W 477 mm (18-25/32")
 H 545 mm (21-7/16")
 D 327 mm (12-7/8")

Dimensions

Weights (Net) 24.0 kg (52.8 lbs)
 (Packed) 26.5 kg (58.5 lbs)

Weights (Net)

24.0 kg (52.8 lbs)
 (Packed) 26.5 kg (58.5 lbs)

(Kenwood follows a policy of continuous advancements in development. For this reason specifications may be changed without notice.)