



### SPECIFICATIONS

<b>Dynamic Power Output (IHF)</b>	40 watts 4Ω	45 watts 8Ω
<b>Continuous Power Output</b>	Each CH. 4Ω 1 kHz	18/18 watts
	Each CH. 8Ω 1 kHz	15/15 watts
	Both CH. 4Ω 1 kHz	15/15 watts
	Both CH. 8Ω 1 kHz	12/12 watts
	Both CH. 8Ω 50~20 kHz	10/10 watts
<b>Harmonic Distortion (at rated)</b>		0.6%
	(at -3 dB rated)	0.2%
<b>Power Band Width</b>		30 Hz ~ 20 kHz
<b>Dumping Factor</b>		50 (8Ω)
<b>Input Sensitivity and Impedance</b>		
<b>Rated Input</b>		
2 Channel	200mV/50 kΩ	
4 Channel	200mV/50 kΩ	
Tape Play	200mV/50 kΩ	
Rec/Play	200mV/100 kΩ	
<b>Maximum Input</b>		
2 Channel	5V/50 kΩ	
4 Channel	5V/50 kΩ	
<b>Output Level and Impedance</b>		
<b>Rated Output</b>		
Output	200mV/5 kΩ	
Tape Rec	200mV/50 kΩ	
Rec/Play	50mV/100 kΩ	
<b>Maximum Output</b>		
Output	3.5V/5 kΩ	
Rec/Play	1V/100 kΩ	
<b>Frequency Response</b>		
Front	20 Hz ~ 20 kHz ±1 dB	
Rear	20 Hz ~ 20 kHz +1 dB -2 dB	
<b>Signal to Noise Ratio</b>		
2 Channel	100 dB	
4 Channel	100 dB	
Front	100 dB	
Rear	100 dB	
<b>Phase Shift</b>		
Front	90° ±10% (25 Hz ~ 18 kHz)	
Rear	90° ±3% (1300 Hz)	
<b>Tone Control (Rear CH.)</b>		
Bass (100 Hz)	±10 dB	
Treble (10 kHz)	±10 dB	
<b>Function</b>		
4CH AUX - SQ - MATRIX - 2CH		
4CH (Push Button)		
FRONT - REAR		
LEFT - RIGHT (REAR)		
<b>Semiconductor</b>		
53 Tr. 24 Di.		
<b>Power Consumption</b>		
60 watts		
48 watts (Regulation law for electrical appliance and material)		
<b>Dimensions</b>		
13-7/32" W 4-1/4" H 10-9/32" D		
<b>Weight</b>		
11.0 lbs.		