



SPECIFICATIONS

FM SECTION

Usable Sensitivity, IHF	3 μ V
Frequency Response	20 Hz to 15,000 Hz, +0, -2 dB
Harmonic Distortion (at 400 Hz, 100% Modulation):	
Mono	Less than 0.8%
Stereo	Less than 0.9%
Signal to Noise Ratio: (at 100% Modulation)	Better than 60 dB
Capture Ratio, IHF	4 dB
Image Frequency Rejection (at 100 MHz)	Better than 50 dB
Harmonics Spurious Response	Better than 70 dB
IF Rejection	Better than 60 dB
Selectivity (alt. channel, IHF)	Better than 35 dB
Stereo Separation	Better than 30 dB at 400 Hz
Output Voltage: (at 400 Hz, 100% Modulation)	1 volt
Antenna Input Impedance	300 ohms Balanced and 75 ohms Unbalanced
Output Impedance	200 ohms
Stereo Noise Filter	Yes (High Frequency Blend circuit)
FM Stereo/Mono Auto Switching	Yes

AM SECTION

Usable Sensitivity, IHF	30 μ V (Ext. Antenna Terminal)
Selectivity, IHF	300 μ V/m (Bar Antenna)
Image Rejection	Better than 25 dB
Output Voltage	0.4 Volt
Power Consumption	15 watts
Dimensions	10-1/4"(W), 4-3/8"(H), 10-9/8"(D)
Weight	8.5 lbs