



**SPECIFICATIONS**

FM SECTION	
USABLE SENSITIVITY (IHF)	: 2.5 $\mu$ V
FREQUENCY RESPONSE	: 20Hz to 15,000Hz $\pm 0$ , $\pm 2$ dB
HARMONIC DISTORTION (at 400Hz, 100% Modulation)	: Mono: Less than 0.0%
	: Stereo: Less than 0.5%
SIGNAL TO NOISE RATIO (at 100% Modulation)	: Better than 60dB
CAPTURE RATIO (IHF)	: 4dB
IMAGE FREQUENCY REJECTION	: Better than 50dB
SPIRIOUS REJECTION	: Better than 75dB
IF REJECTION	: Better than 65dB
AM SUPPRESSION	: Better than 45dB
SELECTIVITY (alt. channel IHF)	: Better than 45dB
MULTIPLY CARRIER SUPPRESSION	: Better than 50dB
STEREO SEPARATION	: Better than 35dB at 1,000Hz
OUTPUT VOLTAGE (at 400Hz, 100% Modulation)	: 1 Volt
ANTENNA INPUT IMPEDANCE	: 300 ohms Balanced and 75 ohms Unbalanced
OUTPUT IMPEDANCE	: 330 ohms
AM SECTION	
USABLE SENSITIVITY (IHF)	: 30 $\mu$ V (Ext. Antenna Terminal)
SELECTIVITY	: Better than 25dB
IMAGE REJECTION	: Better than 45dB
IF REJECTION	: Better than 35dB
OUTPUT VOLTAGE (at 400Hz, 30% Modulation)	: 0.2 Volt
POWER CONSUMPTION	
AC	: 110-120V/220-240V, 50/60Hz 15 watts
DIMENSIONS	
Width	: 165/16" (16.5")
Height	: 5-5/32" (5.156")
Depth	: 11-1/32" (11.031")
WEIGHT	
	: 14 lbs.