



SPECIFICATIONS

- Track System:** 4 track 2 channel stereo
- Motor:** Electronically controlled DC motor
- Applicable Tapes:** C-30, C-60, C-90, C-120
- Tape Speed:** 4.75 cm/sec.
- Wow and Flutter:** Less than 0.09%
- Frequency Response:** 30 ~ 13,000 Hz ± 1 dB (normal tape)
- Characteristic:** 30 ~ 15,000 Hz ± 1 dB (chrome tape)
- Signal to Noise Ratio:**
 - Dolby Off 50 dB (normal tape)
 - Dolby Off 53 dB (chrome tape)
 - Dolby On 58 dB (normal tape)
 - Dolby On 61 dB (chrome tape)
- Recording Bias:** AC type 65 kHz
- Erasing Method:** AC erasing 85 kHz
- Inputs Sensitivity:**
 - MIC 0.2 mV (8k Ω)
 - DIN 0.4 mV (4k Ω)
 - ATT MIC/DIN -12 dB for MIC/DIN
 - LINE 77.5 mV (180k Ω)
 - LINE OUT 0.775V (100k Ω)
 - DIN 0.775V (100k Ω)
- Output Voltage:** Within 80 seconds (IC-60)
- FF, REW Time:** 8.5 W
- Power Consumption:** 430 (W) x 300 (D) x 149 (H) mm
- Dimensions:** 7 kg
- Weight:** Dolby noise reduction system, Input selector (with ATT MIC/DIN), Tape selector equalizer 3 stages
- Functions:** 3-digit tape counter, Record indicating lamp, Cassette holder illuminating lamp and mirror, Mono-mechanism, Full-auto shut-off mechanism
- Accessories:** Audio cord (2 pcs.), Cleaning bar
- Option:** Side board B-6, B-6 is an ornamental side board to be installed on the side of front loading cassette deck KX-620.