



- SPECIFICATIONS**
- RECORD/PLAYBACK SYSTEM:** 4-Track stereo/mono recording and playback
- TAPE:** C-30, C-60, C-90, C-120 Low Noise Tape or Chromium Oxide Tape (CrO₂) cassette
- HEADS:** two head system
- FREQUENCY RESPONSE:** 40 ~ 10,000 Hz (Regular tape)
40 ~ 13,000 Hz (CrO₂ tape)
- SIGNAL-TO-NOISE RATIO:** better than 45 dB (Regular tape)
better than 48 dB (CrO₂ tape)
- WOW and FLUTTER:** less than 0.2%
- HARMONIC DISTORTION (PRE AMP):** less than 0.5% at 0 dB
- FAST WIND/REWIND TIME:** within 70 sec. with C-60 tape
- INPUTS:** Microphone Inputs (Left and Right)
 Sensitivity: -69 dBs (0.25 mV)
 Input Impedance: 50kΩ
 Line Inputs
 Sensitivity: -18 dBs (100mV)
 Input Impedance: 470kΩ
- OUTPUTS:** Line Outputs
 Output level: 0 dBs (0.775 V)
 Optimum load: Impedance: 50kΩ or more
 Headphone Output
 Impedance: 8Ω or more
- DIN CONNECTOR:** Input Sensitivity: -38 dBs (9.8 mV)
 Output Level: 0 dBs (0.775 V)
- HIGH FILTER:** -10 dB at 10kHz
- LEVEL INDICATION:** two VU meters
- SEMICONDUCTORS:** 14 Transistors and 4 Diodes
- POWER REQUIREMENTS:** 20 watts, AC 100, 110, 117, 125, 220, 240V 50/60 Hz
- DIMENSIONS:** 10-1/2" (W), 9" (D), 4" (H)
- WEIGHT:** 7 lbs.
- SUPPLIED ACCESSORIES:** 2 pairs connecting cords tape cassette (one side pre-recorded)