



### SPECIFICATIONS

- No. of Track:** 4 track, 2 channel
- Type of Motor:** DC servo motor
- Usable Tape:** Normal tape (General-purpose tape, Low noise tape) Chrome tape (CrO<sub>2</sub>) ... C-30, C-60, C-90, C-120
- Heads:** Two record/playback super ferrite head and erase
- Tape Speed:** 1-7/8 ips. (4.75 cm/sec.)
- Wow and Flutter:** Less than 0.13%
- Frequency Response Characteristics:** 30 ~ 16,000Hz using chrome tapes. 30 ~ 13,000Hz using low noise tapes.
- Signal to Noise Ratio:** 58dB (DOLBY ON), using chrome tapes. 50dB (DOLBY OFF)
- Recording Bias:** 85 kHz AC type.
- Erasing Method:** AC type.
- Inputs:** Two MIC jacks, Minimum input level 0.24mV/10kΩ, Low impedance (600Ω) for microphone. LINE INPUT - Two LINE INPUTS, Minimum input level 77.5mV/470kΩ.
- Outputs:** Two LINE OUTPUTS, rated output 490mV/100kΩ. One stereo headphone jack for 8 or 16Ω headphones.
- DIN Connector:** One
- Fast Wind/Rewind Time:** Less than 85 seconds for C-60 tapes.
- Built-in Features:** Dolby system, Automatic switching for type of tape, Auto stop mechanism, Cue, Review, Memory rewind, Display of running tape, 3-digit tape counter, Automatic level control, Peak level indicator lamp, Dolby FM/Copy.
- Power Consumption:** 23W
- Dimensions:** 15-7/8 (404 mm) W x 5 (124 mm) H x 9-15/16 (252 mm) D, inches
- Weight:** 5.3 kg
- Accessories Supplied:** Audio 2P cord ..... 2  
Head cleaning set ..... 1