



SPECIFICATIONS

Type:	Stereo Cassette Deck with Dolby System																																	
Track System:	4 Track 2 Channel Stereo/More Recording/Playback																																	
Usable Tape:	Cassette Tape: C-30, C-60, C90 and C120																																	
Heads:	Recording/Playback: Super Ferrite Head (SFH) Erase: Ferrite Head																																	
Motor:	Electronically-Controlled DC Motor																																	
Tape Speed:	4.75 cm/sec (1.78 ips)																																	
Wow and Flutter:	Less than 0.08% (W/RMS) ±0.14% (DIN)																																	
Fast Winding Time:	Less than 62 seconds for C-60 tape																																	
Frequency Response:	Normal: 30 ~ 14,000 Hz (±0.5 dB) Reserve: 30 ~ 16,000 Hz (±1.0 dB) Chromé: 30 ~ 16,000 Hz (±1.0 dB)																																	
Signal to Noise Ratio:	<table border="1"> <thead> <tr> <th colspan="2"></th> <th colspan="2">JIS</th> <th colspan="2">DIN Weighted</th> </tr> <tr> <th></th> <th>Dolby OFF</th> <th>Dolby ON</th> <th>Dolby OFF</th> <th>Dolby ON</th> <th>Dolby ON</th> </tr> </thead> <tbody> <tr> <td>Normal</td> <td>52 dB</td> <td>60 dB</td> <td>48 dB</td> <td>58 dB</td> <td>58 dB</td> </tr> <tr> <td>Reserve</td> <td>54 dB</td> <td>62 dB</td> <td>50 dB</td> <td>58 dB</td> <td>58 dB</td> </tr> <tr> <td>Chromé</td> <td>54 dB</td> <td>62 dB</td> <td>50 dB</td> <td>58 dB</td> <td>58 dB</td> </tr> </tbody> </table>						JIS		DIN Weighted			Dolby OFF	Dolby ON	Dolby OFF	Dolby ON	Dolby ON	Normal	52 dB	60 dB	48 dB	58 dB	58 dB	Reserve	54 dB	62 dB	50 dB	58 dB	58 dB	Chromé	54 dB	62 dB	50 dB	58 dB	58 dB
		JIS		DIN Weighted																														
	Dolby OFF	Dolby ON	Dolby OFF	Dolby ON	Dolby ON																													
Normal	52 dB	60 dB	48 dB	58 dB	58 dB																													
Reserve	54 dB	62 dB	50 dB	58 dB	58 dB																													
Chromé	54 dB	62 dB	50 dB	58 dB	58 dB																													
Recording Bias:	85 kHz AC																																	
Erasing Method:	AC Type																																	
Inputs:	Monophones: X2, 0.24 mV ± 70 dBm/10 kΩ Line: X2, 7.75 mV ± 20 dBm/340 kΩ DIN: 0.45 mV ± 85 dBm/1.2 kΩ (64) W L type																																	
Input Sensitivity/Impedance:	Low impedance (600Ω) for microphone																																	
Outputs:	Line: X2, 490 mV ± 4 dBm/100 kΩ																																	
(Output Level/Load Impedance):	Headphones: X1, 55 mV ± 23 dBm for 8 or 16Ω Headphones DIN: 490 mV ± 4 dBm/100 kΩ																																	
Distortion:	Normal: 1.4% at 1 kHz 0VU Reserve: 2.8% at 1 kHz 0VU Chromé: 1.8% at 1 kHz 0VU																																	
Power Requirements:	AC 120V, 60 Hz USA and CANADA AC 110 ~ 120/220 ~ 240V, 50/60 Hz Others																																	
Power Consumption:	17 watts																																	
Dimensions:	W: 408 mm (16-1/16") D: 252 mm (9-15/16") H: 124 mm (4-7/8")																																	
Weight:	5.5 kg (12 1/8 lb)																																	
Built in Features:	Dolby System, Dolby FM, Auto Tape Selector, Tape Selector (Bias/Equalizer), Auto Shut-off Microphone in All modes, Cue/Review system, Memory Recall, Input Selector (MIC/DIN—LINE), 3 Digit Tape Counter, Recording Volume, Press Marker, Peak Indicator, Tape Running Indicator, Recording Indicator, Dolby NR Indicator, Chromé Tape Indicator, Microphone Jacks, Headphones Jack, DIN Connector, Auto 2P cord																																	
Supplied Accessories:	Head cleaning set: 2 Normal: TOK SDC-90 Reserve: BASF Ferric Chromé C-66 Chromé: TOK SA C-60																																	
Reference Tape:																																		

