



SPECIFICATIONS

AMPLIFIER SECTION	
TOTAL MUSIC POWER:	26 watts (IHF Standard at 8 ohms)
RMS POWER:	9 watts (IHF Standard at 8 ohms)
FREQUENCY RESPONSE:	20—60,000 Hz ±1 dB
POWER BANDWIDTH:	30—25,000 Hz ±1 dB
SIGNAL TO NOISE RATIO:	Phono -60 dB below rated output.
INPUT SENSITIVITY:	Phono 1.5 mV, TAPE PLAY 100 mV
SPEAKER IMPEDANCE:	4—16 ohms
BASS CONTROL:	±10 dB (50 Hz)
TREBLE CONTROL:	±10 dB (10,000 Hz)
LOUDNESS CONTROL:	+10 dB (at 100 Hz), +5 dB (at 10,000 Hz)
TUNER SECTION	
USABLE SENSITIVITY:	FM: 2.5 microvolts (IHF Standard) AM: 10 microvolts (IHF Standard)
FM SIGNAL TO NOISE RATIO:	63 dB (at 98 MHz)
FM IMAGE REJECTION:	50 dB
FM CAPTURE RATIO:	2.5
FM STEREO SEPARATION:	35 dB (at 400 Hz)
FM AUTOMATIC SWITCHING:	Yes
FM STEREO AUTOMATIC INDICATOR:	Yes
FM STEREO NOISE FILTER:	Yes
SPECIAL CIRCUITS:	FM Automatic, SCA Filter, FM Stereo Noise Filter, FM Stereo Automatic Indicator, Headset Jack, Tape Monitor System, Power Transistor Protection Circuit.
POWER CONSUMPTION:	50—60 Hz, 220—230 V, 45 watts
DIMENSIONS:	Width 161/4", Height 6", Depth 133/4"
NET WEIGHT:	20 lbs.