

RIGHT INPUT


- S101 a, 110 b INPUT IMPEDANCE(1.00K, 2.50K, 3.30K)
- S201 a, 102 b, 103 c, 104 d FUNCTION(1: PHONO, 2: PHONO, 3: AUX, 4: AUX, 2: 5: AUX, 3)
- S301 a, 101 b, 102 c, 103 d MODE(1, 1, 2, R, 3 L, 4 R, 5 STEREO, 5 REVERSE)
- S102 a, 104 a MONITOR(1: OFF, 2: ON)
- S103 a, 105 b TAPE-MONITOR SELECTOR(1: TAPE, 2: TAPE, B)

- S104 a, 106 b LOW CUT FILTER(1: OFF, 2: ON)
- S105 a, 107 b HIGH CUT FILTER(1: OFF, 2: ON)
- S106 a, 108 a LOW BOOST(1: OFF, 2: ON)
- S107 a, 109 b PRE-MAIN CONNECT(1: NORMAL, 2: SEPARATE)

- S110 a, 104 b ATTENUATOR(1: OFF, 2: ON)
- S111 a, 101 b MAIN SPEAKER(1: ON, 2: OFF)
- S112 a, 102 b REMOTE SPEAKER(1: ON, 2: OFF)
- S401 BASS(1: DEFEAT, 2: 150HZ, 3: 300HZ, 4: 600HZ)
- S402 TREBLE(1: DEFEAT, 2: 6KHZ, 3: 30KHZ, 4: 15KHZ)

- VR101 a, 101 b VOLUME CONT.
- VR102 a, 102 b BALANCE CONT.
- VR401 BASS CONT.
- VR402 TREBLE CONT.

UNLESS OTHERWISE SPECIFIED ALL RESISTORS ARE IN OHM $\pm 10\%$, 1/4W.
ALL CAPACITORS ARE IN FARAD. THERE MAY BE SLIGHT CHANGES IN THE ACTUAL SET.



SQ-505X