

SPECIFICATIONS

Power Amplifier Section

Continuous Power Output.	40 W + 40 W
Min. RMS power per channel into (T.H.D. 0.06%) 8 ohms from 20 to 20 kHz at rated T.H.D. both channels driven	
Both Channels Driven, at 1000 Hz, 1% Distortion, 4 ohms	50 W + 50 W
Intermodulation Distortion.	no more than 0.06%
Total Harmonic Distortion At rated power into 8 ohms.	0.06%
Power Bandwidth, IHF.	10 Hz to 35 kHz
Damping Factor, at 8 ohms.	40

Preamplifier Section

Input Sensitivity/Impedance

PHONO.	2.2 mV/47 kohms
AUX.	150 mV/39 kohms
TUNER.	150 mV/39 kohms
TAPE	150 mV/39 kohms

PHONO Overload Level 120 mV

Output Level/Impedance 120 mV/2.2 kohms

Frequency Response

PHONO (RIAA)	± 0.5 dB (30 Hz to 15 kHz)
AUX, TAPE.	± 1.0 dB (20 Hz to 20 kHz)

Tone Control

BASS	± 10 dB (70 Hz)
TREBLE	± 10 dB (10 kHz)

Loudness Control, at -30 dB.
 $+10$ dB (70 Hz)
 $+ 5$ dB (10 kHz)

Subsonic Filter 15 Hz, 6 dB/oct.

Signal to Noise Ratio, IHF A network

PHONO.80 dB
AUX.95 dB
TUNER.95 dB
TAPE95 dB

General

Power Requirement. AC 220/240 V,
50/60 Hz

Power Consumption. 290 W

Dimensions

Width	440 mm
Height.	96 mm
Depth	285 mm

Weight, without package. 5.8 kg (12.7 lbs)

*Specifications and design are subject to change without notice.

