

5 . SE - 30A

SPECIFICATIONS

Matching impedance	4 to 16 Ω
Frequency response	20 to 20,000Hz
Sensitivity	115 dB/0.3V at 400Hz
(Measured with B&K's Artificial Ear Model 4153)	
Input (maximum)	2V (each channel)
Speaker	2-3/4" dynamic speaker with a dome of polyester resin
Cord	Retractable coiled cord extensible up to 16.4 feet (5m), with 3-P plug
Weight	Approx. 14 oz (380 g), less cord

NOTE:

Specifications and the design subject to possible modification without notice due to improvements.

PARTS LIST

Key No.	Description	Part No.	
1	Speaker Assembly	SXC-001-0	
2	Protection Board (Left)	SCD-329-A	
3	Protection Board (Right)	SCD-331-A	
4	Case	SXC-002-0	
5	Name Plate	SAL-004-0	
6	Ear pad	SCD-116-B	
7	Head pad	SCD-117-B	
8	Head Band (A)	N63-741-A	
9	Head Band (B)	N63-742-A	
10	Adjusting Knob (Left & Right)	SXC-003-0	
11	Coiled Cord with 3-P Plug	SXC-004-0	
12	Lead Wire	SXC-005-0	
13	Band Shaft	SXC-006-0	
	Packing Case (not for SE-30A/up)	SHG-004-0	
	Leather Case (SE-30A/up only)	SHF-001-0	
	Outer Case (SE-30A/up only)	SHG-005-0	
	Operating Guide	R12-787-0	



