

6 . SE-45

SPECIFICATIONS

Matching impedance	4 to 16 Ω
Frequency response	20 to 20,000 Hz
Maximum input	2V (each channel)
Speaker	2-3/4" (7cm) dynamic speaker with polyester cone
Control	Volume control (each channel)
Cord	Retractable coiled cord extensible up to 16.4 feet (5m), with 3-P plug
Weight	14.87oz. (425g), less cord
Accessories	Y-cord

NOTE:
Specifications and the design subject to possible modification without notice due to improvements.

PARTS LIST

Key No.	Description	Part No.	
1	Speaker Assembly	SXC-008-0	
2	Protection Board (Left)	SXC-027-0	
3	Protection Board (Right)	SXC-028-0	
4	Case	SXC-023-0	
5	Ear pad	SCD-134-A	
6	Head pad	SCD-335-0	
7	Head Band (A)	N63-741-A	
8	Head Band (B)	N63-742-A	
9	Adjusting Knob (Left & Right)	SXC-026-0	
10	Coiled cord with 3-P Plug	SXC-015-0	
11	Lead Wire	SXC-019-0	
12	Band Shaft	SXC-006-0	
13	Knob	SXC-037-0	
14	Volume Control	C81-620-B	
	Packing Case	H93-634-0	
	Y-Cord	D53-639-0	
	Operating Guide	SRB-013-0	



