

10. SE-L20

SPECIFICATIONS

Type	“Open-air” stereo headphones
Speaker	38mm (1-1/2 in) dynamic speaker
Impedance	8Ω
Matching impedance	4 to 16Ω
Frequency response	20 to 20,000 Hz
Sound pressure level	109 dB/0.4V
Maximum input	30mW (each channel)
Cord	2.5m (8-1/4 feet), with 3-P plug
Weight	205g (7oz.), less cord

NOTE:
Specifications and the design subject to possible modification without notice due to improvements.

PARTS LIST

Key No.	Description	Part No.	
1	Speaker	38-705F	
2	Ring (L)	SNK-015-0	
3	Ring (R)	SNK-016-0	
4	Escutcheon Ring	SNB-010-0	
5	Speaker Cover	SXC-035-0	
6	Spring for Speaker Mounting	SNA-003-0	
7	Head Band Assembly	SXC-034-0	
8	Escutcheon Template (L, R)	SAX-010-0	
9	Stopper	SLA-002-0	
10	Screw Cross Pan Head 2.3 x 5		
11	3-P Plug with Cord	SKM-001-0	
12	Cord Clamper	SEF-003-0	
13	Resistor	SCN-001-0	
14	Ear Pad	SXC-069-0	
	Packing Case	SHK-013-0	
	Operating Guide	SRB-010-0	



