

13. SE-L40

SPECIFICATIONS

Type	“Open-air” stereo headphones
Speaker	1-1/2” dynamic speaker
Impedance	8Ω
Matching impedance	4 to 16Ω
Frequency response	20 to 20,000 Hz
Sound pressure level	108dB/0.4V
Maximum input	30mW (each channel)
Cord	9.8 feet (3m), with 3-P plug
Weight	8 oz. (230 g), less cord

NOTE:
Specifications and the design subject to possible modification without notice due to improvements.

PARTS LIST

Key No.	Description	Part No.	
1	Speaker	38-704F	
2	Ring (L)	SNK-046-A	
3	Ring (R)	SNK-047-A	
4	Escutcheon Ring	SNB-010-A	
5	Speaker Cover	SXC-035-C	
6	Spring for Speaker Mounting	SNA-003-0	
7	Head Band Assembly	SXC-034-C	
8	Escutcheon Template (L, R)	SAX-011-0	
9	Stopper	SLA-002-0	
10	Screw Cross Pan Head 2.3 x 5		
11	3-P Plug with Cord	SKM-002-0	
12	Cord Clamper	SEF-003-0	
13	Resistor	SCN-001-0	
14	Ear Pad	SXC-069-0	
	Packing Case	SHG-019-0	
	Decorated Package	SHF-006-0	
	Operating Guide	SRB-011-0	



