



REVISIONS	BY	DATE
1	TM	1-10-64
2	TM	2-19-64

INPUT SELECTOR POSITION	FUNCTION
1	PHONO
2	FM MONO
3	FM MPX AUTOMATIC
4	SUB CH. FILTER
5	AM
6	EXTRA

STEREO SELECTOR POSITION	FUNCTION
1	BAL LEFT
2	BAL RIGHT
3	MONO
4	STEREO
5	REVERSE STEREO
6	LEFT INPUT
7	RIGHT INPUT

THE FOLLOWING CONTROLS IN "LEFT" CHANNEL ARE MECHANICALLY GANGED WITH IDENTICAL CONTROLS IN "RIGHT" CHANNEL:

- 1 - INPUT SELECTOR
- 2 - RUMBLE FILTER
- 3 - BAND WIDE DIST.
- 4 - COMP.
- 5 - LOUDNESS
- 6 - TAPE MONITOR
- 7 - EQUALIZATION

NOTE:

- 1 SWITCHES SHOWN IN MAX. CCW POSITION
- 2 ALL RESISTORS 1/2 W UNLESS NOTED
- 3 ALL VOLTAGES DC ± 15% MEASURED WITH V.O.M.
- 4 NO INPUT SIGNAL AND 117 V LINE
- 5 \* MATCHED RESISTORS

HIGHEST SERIES NUMBERS		
C32	C129	C311
R59	R151	R315
T1	T101	T301
L1	T101	D308

