

CDP-M18/M19

SERVICE MANUAL

Canadian Model

CDP-M18

US Model

Canadian Model

E Model

CDP-M19




Photo : CDP-M18

Model Name Using Similar Mechanism	CDP-190/390
CD Mechanism Name	CDM14-5BD1
Base Unit Name	BU-5BD1

SPECIFICATIONS

Compact disc player

Frequency response	2Hz–20kHz±1dB
Signal to noise ratio	More than 93dB
Dynamic range	More than 90dB
Harmonic distortion	Less than 0.05%
Channel separation	More than 90dB

Power consumption 10W

Dimensions 355×95×300mm (w/h/d)

(approx, including projections) (14×3 3/4×11 1/8 inches)

Weight (approx) 2.8kg (6 lbs 3 oz)

Design and specifications subject to change without notice.

Outputs

LINE OUT (phono jacks)	Output level 2V (at 50 kilohms) Load impedance over 10 kilohms
------------------------	---

PHONES (CDP-M19) (stereo phone jack)	Output level max. 14mW Load impedance 32 ohms
---	--

General


Power requirements	US, Canadian model : 120V AC, 60Hz E, Saudi Arabia, Australian model : 110, 120, 220 or 240VAC adjustable, 50/60Hz
--------------------	--

COMPACT DISC PLAYER
SONY[®]



TABLE OF CONTENTS


<u>Section</u>	<u>Title</u>	<u>Page</u>
SECTION 1. GENERAL		
1-1. Location and Function of Controls.....	2	
SECTION 2. SERVICING NOTES	3	
SECTION 3. ELECTRICAL ADJUSTMENTS	4	
SECTION 4. DIAGRAMS		
4-1. Printed Wiring Boards.....	6	
4-2. Schematic Diagram.....	9	
4-3. IC Block Diagram	12	
SECTION 5. EXPLODED VIEWS	14	
SECTION 6. ELECTRICAL PARTS LIST	18	

HOW TO OPEN THE DISC TRAY WHEN
POWER SWTCH TURNS OFF

Caution : When you work, keep the set horizontal.

**SECTION 1
GENERAL**

1-1. LOCATION AND FUNCTION OF CONTROLS



- | | |
|------|--|
| [1] | POWER switch |
| [2] | Disc tray |
| [3] | Remote sensor |
| [4] | Display window |
| [5] | PROGRAM button |
| [6] | SHUFFLE button |
| [7] | REPEAT button |
| [8] | (headphone) LEVEL control (CDP-M19) |
| [9] | MUSIC SCAN button |
| [10] | PHONES jack (CDP-M19) |
| [11] | FADER button |
| [12] | TIME button |
| [13] | ◀◀▶▶ (AMS* / RMS**) / ◀◀▶▶ (manual search) buttons |
| [14] | ■ (stop)/PGM (program) CLEAR button |
| [15] | ▶▷ (play/pause) button |
| [16] | ▲ (open/close) button |

SAFETY-RELATED COMPONENT WARNING!!

COMPONENTS IDENTIFIED BY MARK OR DOTTED LINE WITH MARK ON THE SCHEMATIC DIAGRAMS AND IN THE PARTS LIST ARE CRITICAL TO SAFE OPERATION. REPLACE THESE COMPONENTS WITH SONY PARTS WHOSE PART NUMBERS APPEAR AS SHOWN IN THIS MANUAL OR IN SUPPLEMENTS PUBLISHED BY SONY.

ATTENTION AU COMPOSANT AYANT RAPPORT
À LA SÉCURITÉ


LES COMPOSANTS IDENTIFIÉS PAR UNE MARQUE SUR LES DIAGRAMMES SCHÉMATIQUES ET LA LISTE DES PIÈCES SONT CRITIQUES POUR LA SÉCURITÉ DE FONCTIONNEMENT. NE REMPLACER CES COMPOSANTS QUE PAR DES PIÈCES SONY DONT LES NUMÉROS SONT DONNÉS DANS CE MANUEL OU DANS LES SUPPLÉMENTS PUBLIÉS PAR SONY.

SECTION 2

SERVICING NOTES

MODEL IDENTIFICATION

—Specification Labels—



US, Canadian model : AC : 120V 60Hz 10W

E, Saudi Arabia,

Australian model : AC : 110–120V, 220–240V
~50/60Hz 10W

NOTES ON HANDLING THE OPTICAL PICK-UP BLOCK OR BASE UNIT

The laser diode in the optical pick-up block may suffer electrostatic breakdown because of the potential difference generated by the charged electrostatic load, etc. on clothing and the human body.

During repair, pay attention to electrostatic breakdown and also use the procedure in the printed matter which is included in the repair parts.

The flexible board is easily damaged and should be handled with care.

NOTES ON LASER DIODE EMISSION CHECK

The laser beam on this model is concentrated so as to be focused on the disc reflective surface by the objective lens in the optical pick-up block. Therefore, when checking the laser diode emission, observe more than 25 cm away from the objective lens.

NOTE ON DISASSEMBLY OF BASE UNIT

Disassembly of BASE UNIT (BU-5BD1) is the same as that of CDP-190/390. Please refer to the CDP-190/390 service manual.

SAFETY CHECK-OUT

After correcting the original service problem, perform the following safety check before releasing the set to the customer:

Check the antenna terminals, metal trim, "metallized" knobs, screws, and all other exposed metal parts for AC leakage. Check leakage as described below.

LEAKAGE TEST

The AC leakage from any exposed metal part to earth ground and from all exposed metal parts to any exposed metal part having a return to chassis, must not exceed 0.5 mA (500 microamperes). Leakage current can be measured by any one of three methods.

1. A commercial leakage tester, such as the Simpson 229 or RCA WT-540A. Follow the manufacturers' instructions to use these instruments.
2. A battery-operated AC milliammeter. The Data Precision 245 digital multimeter is suitable for this job.
3. Measuring the voltage drop across a resistor by means of a VOM or battery-operated AC voltmeter. The "limit" indication is 0.75 V, so analog meters must have an accurate low-voltage scale. The Simpson 250 and Sanwa SH-63Trd are examples of a passive VOM that is suitable. Nearly all battery operated digital multimeters that have a 2V AC range are suitable. (See Fig. A)




Fig. A. Using an AC voltmeter to check AC leakage.


SECTION 3

ELECTRICAL ADJUSTMENTS

1. Perform adjustments in the order given.
2. Use YEDS-18 disc (3-702-101-1) unless otherwise indicated.
3. Use the oscilloscope with more than $10 \text{ M}\Omega$ impedance.


RF Level Check

Procedure :



1. Connect oscilloscope to test point TP (RF) and TP (VC) on BD board.
2. Confirm that RF level and eye pattern is optimum.
Optimum eye pattern means that shape "◇" can be clearly distinguished at the center of the wave form.


RF Signal Reference Waveform (eye pattern)



REFERENCE


E-F Balance Check

Procedure :




1. Connect test point TP (ADJ) and TP (TES) to ground with lead wire.
2. Connect oscilloscope to test point TP (TE O) and TP (VC) on BD board.
3. Turn POWER switch on.
4. Put disc (YEDS-18) in and playback.
5. Confirm that the oscilloscope waveform is symmetrical on the top and bottom in relation to 0V.
6. After check, remove the lead wire connected in step 1.

Note : Take sweep time as long as possible to obtain best waveform.



RF PLL Free-run Frequency Check

Procedure :



1. Turn POWER switch on.
2. Put disc (YEDS-18) in and playback.
3. Confirm that reading on frequency counter is 4.3218MHz.

Focus/Tracking Gain Adjustment

A frequency response analyzer is necessary in order to perform this adjustment exactly.

However, this gain has a margin, so even if it is slightly off, there is no problem. Therefore, do not perform this adjustment.

Focus/tracking gain determines the pick-up follow-up (vertical and horizontal) relative to mechanical noise and mechanical shock when the 2-axis device operate.

However, as these reciprocate, the adjustment is at the point where both are satisfied.

- When gain is raised, the noise when the 2-axis device operates increases.
- When gain is lowered, mechanical shock and skipping occurs more easily.
- When gain adjustment is off, the symptoms below appear.


Symptoms	Gain	Focus	Tracking
• The time until music starts becomes longer for STOP → ▶ PLAY or automatic selection. (◀, ▶ buttons pressed.) (Normally takes about 1 seconds.)	low	low or high	
• Music does not start and disc continues to rotate for STOP → ▶ PLAY or automatic selection. (◀, ▶ buttons pressed.)	-	low	
• Sound is interrupted during PLAY. Or time counter display stops progressing.	-	low	
• More noise during 2-axis device operation.	high	high	

The following is a simple adjustment method.

-Primary Adjustment-

Note : Since exact adjustment cannot be performed, remember the positions of the controls before performing the adjustment.


If the positions after the primary adjustment are only a little different, return the controls to the original position.



Procedure :

1. Keep the set horizontal.
(If the set is not horizontal, this adjustment cannot be performed due to the gravity against the 2-axis device.)
2. Insert disc (YEDS-18) and press ▶ PLAY button.
3. Connect oscilloscope to TP (FEO) and TP (VC) on BD board.
4. Adjustment RV102 on digital board so that the waveform is as shown in the figure below. (focus gain adjustment)

high tracking gain
high fundamental wave)
(than for low gain




VOLT/DIV : 100mV
TIME/DIV : 2mS




- Incorrect Examples (DC level changes more than on adjusted waveform)

VOLT/DIV : 100mV
TIME/DIV : 2mS
low focus gain



VOLT/DIV : 100mV
TIME/DIV : 2mS
high focus gain



5. Connect oscilloscope to TP (TEO) and TP (VC) on BD board.
6. Adjust RV101 on digital board so that the waveform is as shown in the figure below. (tracking gain adjustment)


VOLT/DIV : 1V
TIME/DIV : 2mS




- Incorrect Examples (fundamental wave appears)

low tracking gain


VOLT/DIV : 1V
TIME/DIV : 2mS



Adjustment Location :
[BD board]




[Main board]






**SECTION 4
DIAGRAMS**
**● SEMICONDUCTOR
LEAD LAYOUTS**


CXA1372Q




SEL8864

CXD2500Q
μPD75308GF-545-3B9DTC144EK
FN1L4M-M31
2SD596DV345

RD4.7M-B1


**● SEMICONDUCTOR
LOCATION**

Ref. No.	Location
IC101	C-15
IC102	B-15
IC103	A-15
IC201	G-3
IC202	C-2
IC211	G-6
IC251	C-7
IC252	H-8
IC261	G-8
IC271	G-10
IC291	H-9
Q101	D-16
Q251	H-8
Q271	F-11
Q272	F-11
Q275	G-11
D101	A-16
D201	H-5
D291	H-9
D901	B-3
D902	B-3
D903	B-3
D904	B-3

4-1. PRINTED WIRING BOARDS


Note :


- : parts mounted on the conductor side.
- : Through hole.
- ◆ : Pattern on the side which is seen.
- ◆◆ : Pattern of the rear side.
- EA : Saudi Arabia
- AUS : Australian

Note :


- All capacitors are in μ F unless otherwise noted. pF : $\mu\mu$ F
500V or less are not indicated except for electrolytics and tantalums.
- All resistors are in Ω and $\frac{1}{4}W$ or less unless otherwise specified.
- \triangle : internal component.
- B+** : B+ Line
- B-** : B- Line
- : adjustment for repair.

- Voltage and waveforms are dc with respect to ground under no-signal conditions.
- no mark : PLAY
- () : STOP
- Voltages are taken with a VOM (input impedance 10M Ω). Voltage variations may be noted due to normal production tolerances.
- Waveforms are taken with an oscilloscope. Voltage variations may be noted due to normal production tolerances.
- Circled numbers refer to waveforms.
- Signal path.
- \Rightarrow : CD
- EA : Saudi Arabia
- AUS : Australian

● WAVEFORM




4-2. SCHEMATIC DIAGRAM




4-3. IC BLOCK DIAGRAM


M5285FP




LA6532




CXD2551M




M54641L




LA5601




CXD2500



CXA1372Q



TDA1543



SECTION 5

EXPLODED VIEWS

NOTE:


- The mechanical parts with no reference number in the exploded views are not supplied.
- The construction parts of an assembled part are indicated with a collation number in the remark column.
- Items marked “★” are not stocked since they are seldom required for routine service. Some delay should be anticipated when ordering these items.

- Due to standardization, parts with part number suffix -XX and -X may be different from the parts specified in the components used on the set.
- Color Indication of Appearance Parts Example:
 (RED) ... KNOB, BALANCE (WHITE)
 ↑ ↑
 Cabinet's Color Parts Color
 • AUS : Australian
 EA : Saudi Arabia

The components identified by mark  or dotted line with mark  are critical for safety.
Replace only with part number specified.

Les composants identifiés par une marque  sont critiques pour la sécurité.
Ne les remplacer que par une pièce portant le numéro spécifié.

(1) CHASSIS SECTION




No.	Part No.	Description	Remarks	No.	Part No.	Description	Remarks
1	7-682-548-09	SCREW +BVTT 3X8 (S)		13	7-682-547-04	SCREW +BVTT 3X6 (S)	
2	X-4917-588-3	(M19:US).....PANEL ASSY, FRONT		14	4-933-601-01	FOOT	
	X-4917-589-3	(M19:Canadian)...PANEL ASSY, FRONT		15	*4-885-838-01	(E,EA,AUS)...LABEL, CLASS 1	
	X-4917-590-3	(M19:E,EA,AUS)		16	4-927-341-01	BUTTON (POWER)	
	X-4917-591-3	(M19:E,EA,AUS)		17	*4-921-906-01	FELT	
	PANEL ASSY, FRONT (GRAY)		18	4-927-351-03	PLATE, INDICATION	
	X-4917-594-3	(M18).....PANEL ASSY, FRONT		19	*4-937-504-01	(EXCEPT US)...SHEET (REMOTE CONTROL)	
					*4-937-504-12	(US).....SHEET (REMOTE CONTROL)	
3	*4-933-114-01	ILLUMINATOR		901	*A-4617-196-A	(M19)...MOUNTED PCB, MAIN	
4	*4-933-121-01	HOLDER (LCD)			*A-4617-394-A	(M18)...MOUNTED PCB, MAIN	
5	4-928-635-01	SCREW, +BV (2.6X8) TAPPING		902	*1-632-176-11	PC BOARD, LINE OUT	
6	4-927-339-01	(E,EA,AUS).....PANEL, LOADING (BLACK)		903	*1-634-305-11	PC BOARD, POWER SW	
	4-927-339-12	(M19:Canadian)...PANEL, LOADING		904	*1-632-175-11	PC BOARD, POWER	
	4-927-339-21	(E,EA,AUS).....PANEL, LOADING (GRAY)		905	*1-634-306-11	(M19)...PC BOARD, HP	
	4-927-339-31	(US).....PANEL, LOADING		906	1-535-798-11	JUMPER, FILM (WITH TERMINAL)	
7	3-704-366-01	SCREW (CASE)(M3X8)		CN902A 1-526-929-11	(E).....INLET, AC		
8	4-919-376-31	(BLACK)...CASE		CN902A 1-526-930-11	(US,Canadian)...INLET, AC		
	4-919-376-81	(GRAY)....CASE		CN902A 1-526-931-11	(EA,AUS).....INLET, AC		
9	4-933-116-11	(M19)...KNOB (C, TYPE), LOV		J281 1-566-921-11	JACK, PIN 2P (LINE OUT)		
10	4-820-330-31	SCREW		LCD201 1-808-794-31	DISPLAY PANEL, LIQUID CRYSTAL		
11	7-685-646-79	SCREW +BVTP 3X8 TYPE2 N-S		S901 A 1-571-722-11	(E,EA,AUS)...SWITCH, VOLTAGE SELECTION (120/220V)		
12	*4-927-327-11	(E,EA).....PANEL, BACK					
	*4-927-327-22	(US).....PANEL, BACK					
	*4-927-327-31	(M19:Canadian)...PANEL, BACK					
	*4-927-327-51	(M18).....PANEL, BACK					
	*4-927-327-61	(AUS).....PANEL, BACK					

Note:
The components identified by mark or dotted line with mark are critical for safety.
Replace only with part number specified.


Note:
Les composants identifiés par une marque sont critiques pour la sécurité.
Ne les remplacer que par une pièce portant le numéro spécifié.

(2) CD MECHANISM SECTION (CDM14-5BD1)



No.	Part No.	Description	Remarks	No.	Part No.	Description	Remarks
301	4-933-111-01	CHASSIS (MD)		310	4-933-110-01	HOLDER (MG)	
302	7-621-775-10	SCREW +B 2.6X4		311	A-4675-347-A	MG ASSY	
303	*4-917-583-21	BRACKET, YOKE		312	4-933-134-01	SCREW (+PTPWH M2.6X6)	
304	4-927-649-01	BELT		313	4-917-541-01	SPRING (B)	
305	4-933-109-01	CAM		314	4-933-129-01	HOLDER (BU)	
306	4-927-651-01	PULLEY (S)		315	4-933-108-01	SHAFT (CAM)	
307	4-927-628-01	GEAR (C)		920	*1-632-202-11	PC BOARD, LOADING	
308	4-933-107-01	GEAR (PL)		M191	A-4604-363-A	MOTOR (L) ASSY	
309	4-933-112-01	TABLE, DISK					

(3) OPTICAL PICK-UP BLOCK (BU-5BD1)



Note:
The components identified by mark Δ or dotted line with mark Δ are critical for safety. Replace only with part number specified.

Note:
Les composants identifiés par une marque Δ sont critiques pour la sécurité.
Ne les remplacer que par une pièce portant le numéro spécifié.

No.	Part No.	Description	Remarks	No.	Part No.	Description	Remarks
351	7-685-134-19	SCREW +BTP 2.6X8 TYPE2 N-S		921	*A-4617-161-A	MOUNTED PCB, BD	
352	4-933-126-01	INSULATOR (A)		923	1-575-001-11	WIRE, FLAT TYPE (12 CORE)	
353	4-917-565-01	SHAFT, SLED		924	Δ 8-848-144-11	DEVICE, OPTICAL KSS-240A	
354	7-621-255-15	SCREW +P 2X3		M101	X-4917-504-1	ASSY, MOTOR (SLED)	
355	4-917-567-01	GEAR (M)		M102	X-4917-523-1	ASSY, MOTOR (SPINDLE)	
356	4-917-564-01	GEAR (P), FLATNESS					

SECTION 6

ELECTRICAL PARTS LIST

NOTE:

- Due to standardization, replacements in the parts list may be different from the parts specified in the diagrams or the components used on the set.
- Items marked “★” are not stocked since they are seldom required for routine service. Some delay should be anticipated when ordering these items.
- If there are two or more same circuits in a set such as a stereophonic machine, only typical circuit parts may be indicated and capacitors and resistors in other same circuits may be omitted.

CAPACITORS:MF: μF , PF: $\mu\mu\text{F}$.**RESISTORS**

- All resistors are in ohms.
- F: nonflammable

COILS

- MMH: mH, UH: μH

SEMICONDUCTORS

In each case, U: μ , for example:
 UA...: μA ..., UPA...: μPA ...,
 UPC...: μPC , UPD...: μPD ...

- AUS : Australian
EA : Saudi Arabia

The components identified by mark or dotted line with mark are critical for safety.
Replace only with part number specified.

Les composants identifiés par une marque sont critiques pour la sécurité.
Ne les remplacer que par une pièce portant le numéro spécifié.

Ref.No.	Part No.	Description	Ref.No.	Part No.	Description		
901	*A-4617-196-A	(M19)...MOUNTED PCB, MAIN	C214	1-163-038-00	CERAMIC CHIP 0.1MF	25V	
	*A-4617-394-A	(M18)...MOUNTED PCB, MAIN	C215	1-163-038-00	CERAMIC CHIP 0.1MF	25V	
902	*1-632-176-11	PC BOARD, LINE OUT	C216	1-135-091-00	TANTAL. CHIP 1MF	20% 16V	
903	*1-634-305-11	PC BOARD, POWER SW	C251	1-163-101-00	CERAMIC CHIP 22PF	5% 50V	
904	*1-632-175-11	PC BOARD, POWER	C252	1-163-101-00	CERAMIC CHIP 22PF	5% 50V	
905	*1-634-306-11	(M19)...PC BOARD, HP	C253	1-124-225-00	ELECT 100MF	20% 6.3V	
906	1-535-798-11	JUMPER, FILM (WITH TERMINAL)	C261	1-163-038-00	CERAMIC CHIP 0.1MF	25V	
920	*1-632-202-11	PC BOARD, LOADING	C262	1-164-161-11	CERAMIC CHIP 0.0022MF	10% 50V	
921	*A-4617-161-A	MOUNTED PCB, BD	C263	1-124-225-00	ELECT 100MF	20% 6.3V	
923	1-575-001-11	WIRE, FLAT TYPE (12 CORE)	C264	1-164-161-11	CERAMIC CHIP 0.0022MF	10% 50V	
924	8-848-144-11	DEVICE, OPTICAL KSS-240A	C265	1-124-225-00	ELECT 100MF	20% 6.3V	
C101	1-163-038-00	CERAMIC CHIP 0.1MF	C266	1-124-225-00	ELECT 100MF	20% 6.3V	
C102	1-163-989-11	CERAMIC CHIP 0.033MF	25V	C267	1-163-038-00	CERAMIC CHIP 0.1MF	25V
C103	1-126-094-11	ELECT 4.7MF	10% 25V	C268	1-163-038-00	CERAMIC CHIP 0.1MF	25V
C104	1-163-038-00	CERAMIC CHIP 0.1MF	25V	C271	1-163-038-00	(M19)...CERAMIC CHIP 0.1MF	25V
C105	1-126-154-11	ELECT 47MF	20% 6.3V	C272	1-163-038-00	(M19)...CERAMIC CHIP 0.1MF	25V
C106	1-126-154-11	ELECT 47MF	20% 6.3V	C273	1-163-035-00	(M19)...CERAMIC CHIP 0.047MF	50V
C107	1-126-154-11	ELECT 47MF	20% 6.3V	C274	1-163-035-00	(M19)...CERAMIC CHIP 0.047MF	50V
C108	1-163-038-00	CERAMIC CHIP 0.1MF	25V	C275	1-130-468-00	(M19)...MYLAR 560PF	5% 50V
C109	1-163-038-00	CERAMIC CHIP 0.1MF	25V	C276	1-130-468-00	(M19)...MYLAR 560PF	5% 50V
C110	1-163-989-11	CERAMIC CHIP 0.033MF	10% 25V	C281	1-130-469-00	MYLAR 680PF	5% 50V
C111	1-131-367-00	TANTALUM 22MF	20% 16V	C282	1-130-469-00	MYLAR 680PF	5% 50V
C112	1-164-232-11	CERAMIC CHIP 0.01MF	10% 50V	C291	1-126-096-11	ELECT 10MF	20% 25V
C113	1-164-232-11	CERAMIC CHIP 0.01MF	10% 50V	C292	1-124-225-00	ELECT 100MF	20% 6.3V
C114	1-164-161-11	CERAMIC CHIP 0.0022MF	10% 50V	C293	1-124-225-00	ELECT 100MF	20% 6.3V
C115	1-164-161-11	CERAMIC CHIP 0.0022MF	10% 50V	C294	1-126-160-11	ELECT 1MF	20% 50V
C116	1-163-038-00	CERAMIC CHIP 0.1MF	25V	C295	1-126-096-11	ELECT 10MF	20% 25V
C117	1-163-038-00	CERAMIC CHIP 0.1MF	25V	C296	1-126-096-11	ELECT 10MF	20% 25V
C118	1-163-038-00	CERAMIC CHIP 0.1MF	25V	C297	1-124-584-00	ELECT 100MF	20% 10V
C119	1-164-161-11	CERAMIC CHIP 0.0022MF	10% 50V	C298	1-163-009-11	CERAMIC CHIP 0.001MF	10% 50V
C120	1-163-989-11	CERAMIC CHIP 0.033MF	10% 25V	C299	1-163-038-00	CERAMIC CHIP 0.1MF	25V
C151	1-163-019-00	CERAMIC CHIP 0.0068MF	10% 50V	C901	1-126-939-11	ELECT 1000MF	20% 16V
C152	1-163-038-00	CERAMIC CHIP 0.1MF	25V	C902	1-162-851-11	CERAMIC 0.1MF	20% 16V
C153	1-163-006-11	CERAMIC CHIP 560PF	10% 50V	C903	1-124-887-00	(E,EA,AUS)...ELECT 3300MF	20% 16V
C154	1-164-161-11	CERAMIC CHIP 0.0022MF	10% 50V	CN101	1-568-796-11	SOCKET, CONNECTOR 22P	
C155	1-163-023-00	CERAMIC CHIP 0.015MF	10% 50V	CN102	1-568-795-11	SOCKET, CONNECTOR 12P	
C171	1-163-038-00	CERAMIC CHIP 0.1MF	25V	CN103	*1-564-721-11	PIN, CONNECTOR (SMALL TYPE) 5P	
C172	1-163-038-00	CERAMIC CHIP 0.1MF	25V	CN272	*1-564-495-11	(M19)...PIN, CONNECTOR 2P	
C173	1-163-038-00	CERAMIC CHIP 0.1MF	25V	CN282	*1-564-706-11	PIN, CONNECTOR (SMALL TYPE) 4P	
C174	1-163-038-00	CERAMIC CHIP 0.1MF	25V	CN301	*1-564-707-11	PIN, CONNECTOR (SMALL TYPE) 5P	
C201	1-163-038-00	CERAMIC CHIP 0.1MF	25V	CN901	*1-564-704-11	PIN, CONNECTOR (SMALL TYPE) 2P	
C202	1-163-038-00	CERAMIC CHIP 0.1MF	25V	CN902	1-526-929-11	(E).....INLET, AC	
C203	1-163-038-00	CERAMIC CHIP 0.1MF	25V	CN902	1-526-930-11	(US,Canadian)....INLET, AC	
C211	1-163-809-11	CERAMIC CHIP 0.047MF	10% 25V	CN902	1-526-931-11	(EA,AUS).....INLET, AC	
C212	1-163-011-11	CERAMIC CHIP 0.0015MF	10% 50V	D101	8-719-105-72	DIODE RD4.7M-B1	
C213	1-164-232-11	CERAMIC CHIP 0.01MF	50V	D201	1-808-805-11	DIODE SEL8864	
			D291	8-719-800-76	DIODE 1SS226		

Ref.No.	Part No.	Description	Ref.No.	Part No.	Description
D901	8-719-200-82	DIODE 11ES2	R153	1-216-085-00	METAL GLAZE 33K 5% 1/10W
D902	8-719-200-82	DIODE 11ES2	R154	1-216-085-00	METAL GLAZE 33K 5% 1/10W
D903	8-719-200-82	DIODE 11ES2	R155	1-216-093-00	METAL GLAZE 68K 5% 1/10W
D904	8-719-200-82	DIODE 11ES2	R156	1-216-081-00	METAL GLAZE 22K 5% 1/10W
IC101	8-752-037-33	IC CXA1372Q	R157	1-216-079-00	METAL GLAZE 18K 5% 1/10W
IC102	8-759-821-94	IC LA6532M	R158	1-216-079-00	METAL GLAZE 18K 5% 1/10W
IC103	8-759-633-65	IC M54641L	R159	1-216-079-00	METAL GLAZE 18K 5% 1/10W
IC201	8-759-149-91	IC UPD75308GF-545-3B9	R160	1-216-049-00	METAL GLAZE 1K 5% 1/10W
IC202	8-749-920-83	IC GP1U52XB	R171	1-216-001-00	METAL GLAZE 10 5% 1/10W
IC211	8-752-333-31	IC CXD2500Q	R172	1-216-001-00	METAL GLAZE 10 5% 1/10W
IC251	8-752-334-07	IC CXD2551M	R173	1-216-001-00	METAL GLAZE 10 5% 1/10W
IC252	8-759-990-13	IC TDA1543A-S1	R174	1-216-001-00	METAL GLAZE 10 5% 1/10W
IC261	8-759-633-66	IC M5285FP	R201	1-216-081-00	METAL GLAZE 22K 5% 1/10W
IC271	8-759-981-86	(M19)...IC RC4556MA	R202	1-216-097-00	METAL GLAZE 100K 5% 1/10W
IC291	8-759-821-93	IC LA5601	R203	1-216-097-00	METAL GLAZE 100K 5% 1/10W
J271	1-568-519-21	(M19)...JACK, LARGE TYPE (PHONES)	R204	1-216-081-00	METAL GLAZE 22K 5% 1/10W
J281	1-566-921-11	JACK, PIN 2P (LINE OUT)	R205	1-216-081-00	METAL GLAZE 22K 5% 1/10W
L271	1-424-090-11	(M19)...COIL, LINE FILTER	R206	1-216-081-00	METAL GLAZE 22K 5% 1/10W
L273	1-424-090-11	(M19)...COIL, LINE FILTER	R207	1-216-081-00	METAL GLAZE 22K 5% 1/10W
L291	1-410-658-31	INDUCTOR CHIP 220UH	R208	1-216-081-00	METAL GLAZE 22K 5% 1/10W
L292	1-410-658-31	INDUCTOR CHIP 220UH	R209	1-216-097-00	METAL GLAZE 100K 5% 1/10W
LCD201	1-808-794-31	DISPLAY PANEL, LIQUID CRYSTAL	R211	1-216-061-00	METAL GLAZE 3.3K 5% 1/10W
M101	X-4917-504-1	ASSY, MOTOR (SLED)	R212	1-216-061-00	METAL GLAZE 3.3K 5% 1/10W
M102	X-4917-523-3	ASSY, BASE (SPINDLE)	R213	1-216-073-00	METAL GLAZE 10K 5% 1/10W
M191	A-4604-363-A	MOTOR (L) ASSY	R215	1-216-073-00	METAL GLAZE 10K 5% 1/10W
Q101	8-729-901-01	TRANSISTOR DTC144EK	R216	1-216-113-00	METAL GLAZE 470K 5% 1/10W
Q251	8-729-141-75	TRANSISTOR 2SD596-DV345	R217	1-216-037-00	METAL GLAZE 330 5% 1/10W
Q271	8-729-141-75	(M19)...TRANSISTOR 2SD596-DV345	R218	1-216-049-00	METAL GLAZE 1K 5% 1/10W
Q272	8-729-141-75	(M19)...TRANSISTOR 2SD596-DV345	R219	1-216-055-00	METAL GLAZE 1.8K 5% 1/10W
Q273	8-729-113-66	(M19)...TRANSISTOR FN1L4M-M31	R220	1-216-057-00	METAL GLAZE 2.2K 5% 1/10W
R101	1-216-097-00	METAL GLAZE 100K 5% 1/10W	R241	1-216-018-00	METAL GLAZE 51 5% 1/10W
R102	1-216-097-00	METAL GLAZE 100K 5% 1/10W	R242	1-216-018-00	METAL GLAZE 51 5% 1/10W
R103	1-216-091-00	METAL GLAZE 56K 5% 1/10W	R243	1-216-018-00	METAL GLAZE 51 5% 1/10W
R104	1-216-099-00	METAL GLAZE 120K 5% 1/10W	R244	1-216-018-00	METAL GLAZE 51 5% 1/10W
R105	1-216-069-00	METAL GLAZE 6.8K 5% 1/10W	R245	1-216-018-00	METAL GLAZE 51 5% 1/10W
R106	1-216-061-00	METAL GLAZE 3.3K 5% 1/10W	R251	1-216-041-00	METAL GLAZE 470 5% 1/10W
R107	1-216-114-00	METAL GLAZE 510K 5% 1/10W	R252	1-216-051-00	METAL GLAZE 1.2K 5% 1/10W
R108	1-216-105-00	METAL GLAZE 220K 5% 1/10W	R253	1-216-045-00	METAL GLAZE 680 5% 1/10W
R109	1-216-061-00	METAL GLAZE 3.3K 5% 1/10W	R254	1-216-037-00	METAL GLAZE 330 5% 1/10W
R110	1-216-049-00	METAL GLAZE 1K 5% 1/10W	R255	1-216-057-00	METAL GLAZE 2.2K 5% 1/10W
R111	1-216-049-00	METAL GLAZE 1K 5% 1/10W	R261	1-216-065-00	METAL GLAZE 4.7K 5% 1/10W
R112	1-216-083-00	METAL GLAZE 27K 5% 1/10W	R262	1-216-045-00	METAL GLAZE 680 5% 1/10W
R113	1-216-071-00	METAL GLAZE 8.2K 5% 1/10W	R263	1-216-045-00	METAL GLAZE 680 5% 1/10W
R114	1-216-105-00	METAL GLAZE 220K 5% 1/10W	R271	1-216-019-00	(M19)...METAL GLAZE 56 5% 1/10W
R152	1-216-073-00	METAL GLAZE 10K 5% 1/10W	R272	1-216-019-00	(M19)...METAL GLAZE 56 5% 1/10W

<u>Ref.No.</u>	<u>Part No.</u>	<u>Description</u>
R273	1-216-053-00	(M19)...METAL GLAZE 1.5K 5% 1/10W
R274	1-216-053-00	(M19)...METAL GLAZE 1.5K 5% 1/10W
R275	1-216-097-00	(M19)...METAL GLAZE 100K 5% 1/10W
R281	1-216-049-00	METAL GLAZE 1K 5% 1/10W
R282	1-216-049-00	METAL GLAZE 1K 5% 1/10W
R291	1-216-298-00	METAL GLAZE 2.2 5% 1/10W
R293	1-216-025-00	METAL GLAZE 100 5% 1/10W
RV101	1-238-016-11	RES, ADJ, CARBON 10K (TRACKING GAIN)
RV102	1-238-016-11	RES, ADJ, CARBON 10K (FOCUS GAIN)
RV271	1-238-748-11	(M19)...RES, VAR, CARBON 1K/1K(LEVEL)
S101	1-572-085-11	SWITCH, LEAF (LIMIT SW)
S191	1-572-086-11	SWITCH, LEAF (OUT SW)
S192	1-572-086-11	SWITCH, LEAF (IN SW)
S201	1-554-303-21	SWITCH, KEY BOARD (MUSIC SCAN)
S202	1-554-303-21	SWITCH, KEY BOARD (TIMES)
S203	1-554-303-21	SWITCH, KEY BOARD (OPEN/CLOSE)
S204	1-554-303-21	SWITCH, KEY BOARD (■)
S205	1-554-303-21	SWITCH, KEY BOARD (▷/◁)
S206	1-554-303-21	SWITCH, KEY BOARD (◀◀/◀◀)
S207	1-554-303-21	SWITCH, KEY BOARD (▶▶/▶▶)
S208	1-554-303-21	SWITCH, KEY BOARD (PGM)
S209	1-554-303-21	SWITCH, KEY BOARD (SHUFFLE)
S210	1-554-303-21	SWITCH, KEY BOARD (REPEAT)
S211	1-554-303-21	SWITCH, KEY BOARD (FADER)
S291	1-571-305-11	SWITCH, PUSH (1 KEY)(POWER)
S901	▲1-571-722-11	(E,EA,AUS)...SWITCH, VOLTAGE SELECTION (120/220V)
T901	▲1-449-824-11	(US,Canadian)...TRANSFORMER, POWER
T901	▲1-450-011-11	(E,EA,AUS).....TRANSFORMER, POWER
X201	1-567-775-11	VIBRATOR, CERAMIC
X251	1-567-908-11	VIBRATOR, CRYSTAL

ACCESSORY & PACKING MATERIAL

▲1-555-074-11	(AUS).....CORD, POWER
▲1-556-280-00	(E).....CORD, POWER
▲1-558-834-11	(US,Canadian)...CORD, POWER
▲1-558-835-11	(EA).....CORD, POWER
1-559-533-11	CORD, CONNECTION
▲1-569-007-11	(E)....ADAPTOR, CONVERSION 2P
▲1-569-008-11	(EA)...ADAPTOR, CONVERSION 2P
3-750-716-11	(M19:EXCEPT US)...MANUAL, INSTRUCTION
3-750-716-21	(US).....MANUAL, INSTRUCTION
*3-795-629-11	INSTRUCTION
*4-922-998-01	CUSHION
*4-927-393-11	(M19)...INDIVIDUAL CARTON
*4-927-393-21	(M18)...INDIVIDUAL CARTON

Note:
The components identified by mark ▲ or dotted line with mark ▲ are critical for safety. Replace only with part number specified.

Note:
Les composants identifiés par une marque ▲ sont critiques pour la sécurité.
Ne les remplacer que par une pièce portant le numéro spécifié.

CDP-M18/M19

SONY SERVICE MANUAL

Canadian Model
CDP-M18

US Model
Canadian Model
E Model
CDP-M19

CORRECTION-1

Correct your service manual as shown below.

 : indicates corrected portion.

Page	INCORRECT	CORRECT
4	<p>E-F Balance Check Procedure :</p> <p>1. Connect test point TP (ADJ) to ground with lead wire.</p>	<p>E-F Balance Check Procedure :</p> <p>1. Connect test point TP (ADJ) to ground and <u>TP (TES)</u> to <u>TP (VC)</u> with lead wire.</p> 