SECTION 4
DIAGRAMS

4-1. MOUNTING DIAGRAM

4-2. SCHEMATIC DIAGRAM

Note:

- All capacitors are in μF unless otherwise noted. pF : $\mu\mu$F 50WV or less are not indicated except for electrolytics and tantalums.
- All resistors are in ohms, ¼W unless otherwise noted. kΩ : 1000 Ω, MΩ : 1000 kΩ
- : nonflammable resistor.
- : fusible resistor.
- : panel designation.
- : adjustment for repair.
- : B+ bus.
- : B– bus.
- Readings are taken under no-signal conditions with a VOM (20 kΩ/V).
  no mark: When power switch (S1) turns on with tonearm set on arm rest.
  ( ): at 33 rpm with tonearm set on arm rest.
- Switches

Ref. No.	Switch	Position
S1	POWER	ON
S2	Cam-switch arm position detection	(1)
S3	START/STOP	–
S4	ARM LIFTER	–
S5	REPEAT	–
S6	SPEED 45/33	–
S7	OPEN/CLOSE	–
S8	to stop opening the module	OFF
S9	to stop closing the module	OFF
S10	MUTING	PLAY

Note: The components identified by shading and mark ⚠ are critical for safety. Replace only with part number specified.